

REQUEST FOR CORRECTION OF APPARENT ERROR

Commissioner, Patent Office Esq.

1. Indication of International Application

PCT/JP2005/010790

2. Applicant

Appellation MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD.

Address 1006, Oaza Kadoma, Kadoma-shi, Osaka  
571-8501 JAPAN

Nationality JAPAN

Residence JAPAN

3. Agent

Name (11510) Attorney TAKAMATSU Takeshi

Address Eikoh Patent Office, 13th floor, ARK Mori  
Building, 12-32, Akasaka 1-chome,  
Minato-ku, Tokyo 107-6013 Japan

4. Object of correction

(1) Page 8 of the specification

5. Content of correction Recited in attached sheet

(1) Correct the description "[Fig. 13] (a) is a perspective view showing the configuration of an electromechanical signal selection device according to Embodiment 5 of the present invention." as "[Fig. 13] A perspective view showing the configuration of an electromechanical signal selection device according to Embodiment 5 of the present invention."

6. List of Attached Documents

New sheet of page 8 of the specification

micro-vibrator; and (b) is a diagram showing a vibrating state of the micro-vibrator.

[Fig. 11] (a) is a perspective view showing the configuration of an electromechanical signal selection device according to Embodiment 3 of the present invention, and (b) is a perspective view showing a modification of the electromechanical signal selection device in Fig. 11(a).

[Fig. 12] (a) is a perspective view showing the configuration of an electromechanical signal selection device according to Embodiment 4 of the present invention, and (b) is a perspective view showing the configuration of an electromechanical signal selection device according to a modification of Embodiment 4 of the present invention.

[Fig. 13] A perspective view showing the configuration of an electromechanical signal selection device according to Embodiment 5 of the present invention.

[Fig. 14] (a) is a perspective view showing the structure of a micro-vibrator according to Embodiment 6 of the present invention, and (b) is a perspective view showing the structure of a micro-vibrator according to a modification of Embodiment 6 of the present invention.

[Fig. 15] Graphs showing signal selection characteristics according to Embodiment 7 of the present invention: in which (a) is a graph showing the case where the material of a micro-vibrator shows a linear or nonlinear change in electric